

- > Proudly New Zealand owned and locally manufactured
- > **Service Support: 24 hours a day seven days a week**
- > Innovative seamless design integration
- > **Eye catching aesthetics**
- > Slimline profile
- > **Engineered for performance in high density traffic flow environments**
- > To suit Timber, Aluminium Framed, Frameless Glass, Cavity Sliding and Servery window applications
- > **Custom made to suit your project needs**
- > A host of actuation options available
- > **Interface with all Access control options**
- > Device Manager Control Pad or key switching options
- > **One million cycle tested to AS5007-2007**
- > Over engineered to move door weights up to 380kg

- > **Extremely safe operation featuring automatic reversing. Installed in compliance to the safety elements of AS5007-2007**
- > Built in UPS System (Uninterrupted Power Supply)
- > **Hinged pelmet design**
- > High security locking module incorporated in the Motor
- > **Christchurch, Wellington, Hamilton, Auckland, Whangarei, Palmerston North, Dunedin, Tauranga, New Plymouth, Napier, Central Otago**
- > Steel reinforced belt
- > **Whisper quiet operation**
- > Climate control function available
- > **Tailored maintenance packages available**
- > Energy efficient
- > **Market leading Warranties**

Manufactured and installed for compliance to the BCA & AS5007-2007



PROUDLY NEW ZEALAND OWNED AND OPERATED  
AUTOMATIC ENTRY SOLUTIONS

Model TF340



#### Commercial Door Services

Branches in:  
Auckland, Hamilton, Whangarei,  
Tauranga, Wellington, Palmerston North,  
New Plymouth, Napier, Christchurch,  
Dunedin, Central Otago  
Ph: 0800 863 493  
Email: info@cid.co.nz  
www.commercialdoors.co.nz



#### Sensormatic Manufacturing

Facility  
Ph: 0800 863 493  
40 Durham Street South, Sydenham  
Christchurch  
www.sensormaticdoors.co.nz





MODEL	TF340S	TF340H
Motor	90w	300W
Bi-Parting	Y	Y
Drive	Steel Reinforced Belt	Steel Reinforced Belt
Single	Y	Y
BiSliding/Telescopic	Y	Y
Aluminium Doors	Y	Y
Panic Breakout	N	Y
Glass Doors	Y	Y
Timber Doors	Y	Y
Profile Height/Depth	169mmx190mm	169mmx190mm
Pelmet	Y	Y
Electric Motor Lock	opt	opt
Keypad Programmable Mode	Y	Y
Master Keyed Key Switching	opt	opt
Panic Lock	opt	opt
Total Door Weight	240kg	360kg
Weight per Leaf	120kg	185kg
Maximum Width	<1300mm*	8000
Speed per Bi-Parting Doors	25-1300mm/sec	25-1300mm/sec
Door Open Dwell Time	1-60 sec	1-60 sec
Airlock Function	Y	Y
Climate Control (reduced opening)	Y	Y
Keypad Control	Y	Y
Keyed Mode Switch Control	opt	Y
Sensors	Microwave	Microwave
Safety Stop	Y	Y
Safety Reverse	Y	Y
Fire Alarm Interface	Y	Y
Building Management Interface	Y	Y
Chime	opt	opt
Access Interface	Y	Y
Exit Only Function	Y	Y
Power Supply	240v/10amp	240v/10amp
Failsafe/Failsecure	Y	Y
One million cycle tested to AS 5007-2007	Y	Y

\* Based on door height of approx 2400mm. (Please confirm with your representative).

**< Motor & Gearbox**

Designed to suit heavy duty applications, this model can operate up to 120kg per leaf in a wide range of applications. This unit is ideal for supermarkets, office buildings and retail shops. Incorporating an integral hall effect counter, this motor and gearbox provides perfect door positioning and whisper quiet operation.

**< Master Key Options**

For maximum entry security

Standard Key Options >

**< Intelligent Controller**

Using the latest Microcomputer technology we provide safe and intelligent control of the doors at all times. The Microcomputer accurately monitors every movement of the door and can also provide automatic compensation based on climatic conditions such as wind loads and normal wear.

The Microcomputer has an inbuilt, self monitored and recalibrating feature to always reprogram itself back to it's peak performance settings. The Sensormatic door operators are manufactured utilising high quality componentry with a primary focus on providing cost effective, trouble free and ongoing door opening solutions.

**< Tailored Opening Solutions**

Tailored opening functions – Climate control / Courier mode reduced opening settings for better efficiency and security.

**< Quiet & Smooth**

Vibration dampened – ensuring a quiet and smooth operation at all times.

Reset Switch >

**< Track**

All operators come standard with a aluminium track Anodised to 25 micron for increased strength

**< Sensors**

Are fully monitored computerized microwave and infrared sensors with adjustable sensitivity, range and selectable zone detection pattern.

**< Belt**

A "H" section steel reinforced belt provides both whisper quiet operation and maximum security when coupled with electric motor locking.

**< Battery Back Up**

Is supplied to maintain locking in the event of a power failure as well as to open the doors on an emergency signal when required.

Push Button Options >

**< Electric Motor Lock**

Considered the bench mark for high security applications. Electric Motor Locking provides instant peace of mind knowing that regardless of door alignment the doors will lock providing instant security.

**< Device Manager**

- > Access control pad option
- > Large display
- > Self Diagnostic
- > User friendly

Floor Guides >

**< Pelmet Section**

Aesthetically pleasing narrow pelmet section coloured to suit your project.

**Failsafe**

On Power failure the doors will open or operate normally by using the built in UPS as per AS 5007-2007.

**Warranties**

- > 5 years motor and gearbox
- > 2 years parts
- > 12 months labour
- > Extended warranties on periodic maintenance

